

MODEL		P <sub>2</sub>		DELIVERY n ≈ 2850 r/min												
1~ 220V/240V	3~ 380V/415V	kw	HP	Q m <sup>3</sup> /h l/min	0	0.6	1.2	1.8	2.4	3.0	3.6	4.2	4.8	5.4	6.0	6.6
4SPM5-4	4SP5-4	0.37	0.50	H(m)	0	10	20	30	40	50	60	70	80	90	100	110
4SPM5-6	4SP5-6	0.55	0.75		25	25	24	23	22	21	20	19	17	15	12	9
4SPM5-8	4SP5-8	0.75	1.0		38	37	35	34	33	31	30	28	25	22	18	13
4SPM5-10	4SP5-10	1.1	1.5		51	49	47	45	44	42	40	37	34	29	24	18
4SPM5-12	4SP5-12	1.1	1.5		64	61	59	57	55	52	50	47	42	37	30	22
4SPM5-14	4SP5-14	1.5	2.0		77	74	71	68	66	63	60	56	51	44	36	27
4SPM5-17	4SP5-17	1.5	2.0		89	86	82	79	77	73	70	65	59	51	42	31
4SPM5-21	4SP5-21	2.2	3.0		108	104	100	96	93	89	85	79	72	62	51	38
4SPM5-25	4SP5-25	2.2	3.0		134	129	123	119	115	110	105	98	89	77	63	47
-	4SP5-29	3.0	4.0		159	154	147	142	137	131	125	117	106	92	75	56
-	4SP5-33	3.0	4.0		185	178	170	164	159	152	145	135	123	106	87	65
-	4SP5-38	4.0	5.5		210	203	194	187	181	173	165	154	140	121	99	74
-	4SP5-43	4.0	5.5		242	233	223	215	208	199	190	177	161	139	114	85
-	4SP5-50	5.5	7.5		274	264	253	244	235	226	215	201	183	158	129	97
-	4SP5-57	5.5	7.5		318	307	294	283	274	262	250	233	212	183	150	112
					363	350	335	323	312	299	285	266	242	209	171	128