


FS-98D



≅ 2900 1/min

CARATTERISTICHE IDRAULICHE

HYDRAULIC FEATURES

CARACTERISTICAS HIDRAULICAS / CARACTERISTIQUES HYDRAULIQUES / HYDRAULISCHE EIGENSCHAFTEN / CARACTERÍSTICAS HIDRÁULICAS

Tipo Type	Motore Motor		In(A)		— —		Q	H								
	kW	HP	3~ 400 V	1~... 230 V	μF	V		U.S.g.p.m.	0	8,8	13,2	17,6	22	26,4	31	35
								m³/h	0	2	3	4	5	6	7	8
							l/min	0	33,3	50	66,7	83,3	100	117	133	
FS-98 D/6*	0,55	0,75	1,6	5,7	20	450	40	37	35	32	28	23	17	11		
FS-98 D/8*	0,75	1	2,1	7	30	450	53,5	49	46	43	38	30	22	14		
FS-98 D/11*	1,1	1,5	2,9	9,6	40	450	73,5	68	64	59	52	42	30	19		
FS-98 D/15*	1,5	2	3,8	11,5	50	450	95	92	87	80	70	56	41	26		
FS-98 D/19*	2,2	3	6,3	14,7	70	450	120	116	110	101	89	71	52	33		
FS-98 D/22*	2,2	3	6,3	14,7	70	450	139	135	127	117	103	82	60	38		
FS-98 D/26	3	4	7,8	19,1	100+100	450	164	159	150	138	121	97	71	45		
FS-98 D/30	3	4	7,8	19,1	100+100	450	189	183	173	159	140	111	81	51		
FS-98 D/35	4	5,5	10,5	23,9	130+100	450	221	214	202	186	163	130	95	60		
XFS-98 D/39	4	5,5	10,5	23,9	130+100	450	247	238	225	207	179	145	106	66		
XFS-98 D/47	5,5	7,5	14,4	-			297	287	271	250	220	175	128	80		
XFS-98 D/54	5,5	7,5	14,4	-			342	330	311	287	252	200	146	92		